

TT-Surubelnita-dinamometrica-cu-ceas-max-500cNm

Versatile Torque Measuring Screwdrivers for any manufacturing environment

- Absolute accuracy.** Unique torsion bar mechanism to ensure total precision
- Dual scale.** Dial provides efficient measurement in Metric and Imperial torque units in both directions, delivering flexibility and minimising tool investment
- Ease of use.** Lightweight materials. Tools can be used by operators at any skill level
- Long tool life.** High quality, robust construction: stainless steel shaft, attractive coloured aluminium handle and sturdy dial

- Measure Process Conformity.** Unique memory function enables these tools to carry out the Just Move and Break Loose Quality Auditing Tests
- No risk of tool damage.** Overload Protection System with unique positive contact mechanism
- Operational versatility.** Torque can be measured as it is applied (Track mode) or when the maximum torque value has been recorded (Peak mode)








Additional features

- Calibration Service enables tools to be kept accurate and up to date. **See page 82**
- Two year warranty provides additional peace of mind
- Range of accessories provides versatility. **See pages 72-79**

For more information: Tool Selector; gedore-torque.com/tool-selector Telephone; +44 (0) 1483 894 476 Videos; www.youtube.com/gedore-torque Email; salesandrepairs@gedore-torque.com

Want to know how to use this tool?

 Watch our video

Order Code	Model	← Calibrated Range →				Drive	k mm	g	Accuracy	ISO 6789 Class	
		ISO	Imperial	Imperial	Imperial						
017400	TT 50 FH	10-50 cN.m	2 cN.m	14-70 ozf-in	2 ozf-in		178	190	+/- 6%	1D	✓
017500	TT 100 FH	20-100 cN.m	4 cN.m	28-140 ozf-in	4 ozf-in		178	190	+/- 6%	1D	✓
017600	TT 250 FH	50-250 cN.m	10 cN.m	4-20 lbf-in	0.5 lbf-in		250	465	+/- 6%	1D	✓
017700	TT 500 FH	100-500 cN.m	20 cN.m	8-40 lbf-in	1 lbf-in		250	465	+/- 6%	1D	✓